PIPE CLAMP & HANGER CATALOGUE

Manufactured in India | Trusted Worldwide Since 1957

Ferry International

We Provide Fixing Solutions

Address: Plot No. E-2, Sector B-1, Trans Delhi Signature City, Ghaziabad 201103, India
Phone: +91-9990877399 | Email: ferryinternational11@gmail.com
Website: www.ferry-international.com

Rubber Lined Split Clamp

Rubber Lined Split Clamps are designed to support insulated or non-insulated pipes, providing excellent vibration damping and noise reduction. Ideal for HVAC, plumbing, and mechanical applications.

Key Features:

- Rubber lining absorbs vibration and prevents corrosion
- Zinc plated or hot-dip galvanized steel body
- Suitable for M8/M10 threaded rods
- Available in sizes from 17mm to 212mm

Technical Size Chart:

Range (mm)	Connection Nut Size
17-20	M8/M10
20-25	M8/M10
26-30	M8/M10
32-36	M8/M10
38-44	M8/M10
47-51	M8/M10
53-58	M8/M10
60-64	M8/M10
63-67	M8/M10
74-80	M8/M10
81-86	M8/M10
87-92	M8/M10
107-112	M8/M10
113-118	M8/M10
160-167	M8/M10
200-212	M8/M10

Sprinkler Clamp

Sprinkler Clamps are used to support fire-fighting pipelines and sprinkler systems. They provide secure, vibration-resistant support for overhead installations.

Key Features:

- Galvanized steel body
- Compatible with standard threaded rods
- Used in fire-fighting pipelines
- Available in multiple diameters

Technical Size Chart:

Size (Inches)	Rod Size (mm)
1/2	10
3/4	10
1	10
1-1/4	10
1-1/2	10
2	10
2-1/2	10
3	10
4	10
6	10
8	12

Cable Clamp

Cable Clamps are used for routing and securing electrical, data, or communication cables neatly along surfaces. They prevent strain and damage to cables in industrial setups.

Key Features:

- Stainless steel with EPDM lining
- Ideal for electrical and data cable routing
- Compact design for easy mounting

Technical Size Chart:

Size (Inch)	Inner Diameter (Inch)	Slotted Hole (Inch)	Hole Diameter (Inch)
1/2	0.500	0.375	0.268
3/4	0.750	0.375	0.268
1	1.000	0.375	0.268
3/8	0.375	0.375	0.268
5/8	0.625	0.375	0.268

U Clamp

U Clamps are U-shaped fasteners designed to hold and secure round pipes against walls or supports. Commonly used in plumbing, solar, and mechanical systems.

Key Features:

• Available in mild steel, HDG, and stainless steel
• High strength for heavy pipe applications
• Easy to install with nut and bolt assembly

Technical Size Chart:

Size (Inch)	Diameter (mm)	Typical Weight (g)
3/4	19	50
1	25	75
1 1/4	32	100
1 1/2	38	120
2	50	150
2 1/2	63	200
3	76	250
4	102	350
6	152	500

Clevis Hanger

Clevis Hangers provide vertical pipe support for suspended pipelines. They are commonly used in HVAC and fire-fighting systems for strong, adjustable support.

Key Features:

• Hot-dip galvanized or stainless steel options
• Adjustable vertical alignment
• Tested for load up to 8.63 kN

Technical Size Chart:

Size (Inch)	Recommended Load (kN, Max.)
3/4	2.71
1	3.24
1-1/4	3.24
1-1/2	3.24
2	3.24
2-1/2	6.00
3	6.00
4	6.36
6	8.63

About Ferry International

Ferry International is a trusted manufacturer and exporter of industrial fasteners, anchor bolts, and pipe support systems since 1957. Based in Ghaziabad (Delhi NCR), we serve clients across India and globally.

Contact Us

Phone: +91-9990877399 | Email: ferryinternational11@gmail.com
Website: www.ferry-international.com
Address: Plot No. E-2, Sector B-1, Trans Delhi Signature City, Ghaziabad, India

Trusted by Engineers Since 1957